

# Useful HTML tags and their attributes

## < B > Body tag and attributes

<BODY>...</BODY>	Contains the viewed portion of the document
<BODY bgcolor="color">	Sets the color of the background in hexadecimal code
<BODY background="filename.xxx">	Sets an image as a page's background (wallpaper)
<BODY text="color">	Specifies the color of normal text in hexadecimal code
<BODY link="color">	Specifies the default color of unvisited links in hexadecimal code
<BODY alink="color">	Specifies the color of links on click in hexadecimal code
<BODY vlink="color">	Specifies the color of followed links in hexadecimal code

## < F > Font tag and attributes

<FONT>...</FONT>	Changes font attributes for text within the tags
<FONT size="value">...</FONT>	Sets the font to a size from 1 to 7, with 1 the smallest and 7 the largest
<FONT face="name">...</FONT>	Sets the font face
<FONT color="color">...</FONT>	Sets the font color using hexadecimal code

## < I > Image tag and attributes

<IMG>	Embeds an image in the document at the location of the tag
<IMG src="url" alt="text">	Adds an image with a text description
<IMG src="url" alt="text" align="direction">	Aligns an image to the left, right, center, bottom, or top
<IMG src="url" alt="text" border="number">	Sets the size of the border around an image
<IMG src="url" alt="text" height="pixels">	Sets the height of an image
<IMG src="url" alt="text" width="pixels">	Sets the width of an image
<IMG src="url" alt="text" hspace="pixels">	Sets a horizontal margin to be placed around an image
<IMG src="url" alt="text" vspace="pixels">	Sets a vertical margin to be placed around an image
<IMG src="url" alt="text" usemap="map-name">	Designates an image as a client-side image map

## < A > Anchor tag and attributes

<A>...</A>	Designates the origin and destination of a hyperlink
<A HREF="url">...</A>	Creates a hyperlink
<A HREF="#NAME">...</A>	Links to a target location in the current page
<A HREF="URL#NAME">...</A>	Links to a target location in a page outside your site
<A NAME="NAME">...</A>	Sets a target location within a document
<A HREF="mailto:email">...</A>	Creates a mailto link
<b>Optional Attributes</b>	
<A HREF="?" target="?">...</A>	Specifies where the linked-to document is to be placed
<A HREF="?" rel="?">...</A>	Sets up a relationship between the linked-to document and the current page
<A HREF="?" rev="?">...</A>	Sets up a reverse relationship between the current page and the linked-to document

## <T> Table tag and attributes

<TABLE>...</TABLE>	Generates a table
<TABLE border="pixels">	Sets the size of cell borders
<TABLE cellspacing="pixels">	Sets the amount of space between cells
<TABLE cellpadding="pixels">	Sets the amount of space between a border and cell content
<TABLE height="pixels" or "%">	Sets the height of a table
<TABLE width="pixels" or "%">	Sets the width of a table
<TD>...</TD>	Defines a table data cell
<TD colspan="columns">	Sets a cell to span columns
<TD rowspan="rows">	Sets a cell to span rows
<TD nowrap>	Prevents the lines within a cell from wrapping
<TH>...</TH>	Defines a table header with bold, centered table data
<TR>...</TR>	Defines a table row
<TR align="?"> or <TD align="?">	Aligns the contents of a row or cell to the left, right, or center
<TR valign="?"> or <TD valign="?">	Sets the vertical alignment of a row or cell to the top, middle, or bottom

## <FR> Frame tag and attributes

<FRAMESET>...</FRAMESET>	Specifies the layout of subsections in the main browser window
<FRAMESET rows="value,value">	Defines the rows within a frameset
<FRAMESET cols="value,value">	Defines the columns within a frameset
<NOFRAMES>...</NOFRAMES>	Provides alternate content for browsers that do not support frames
<FRAME src="?">	Defines the appearance and content of a single frame
<FRAME name="name">	Labels the frame for targeting by other frames
<FRAME marginwidth="#">	Sets the margin width of a frame
<FRAME marginheight="#">	Sets the margin height of a frame
<FRAME scrolling="value">	Creates a frame scrollbar
<FRAME noresize>	Prevents the resizing of a frame

## <FO> Form tag and attributes

<FORM>...</FORM>	Generates a container for all form elements
<FORM action="url">	Designates the path of the script to process input from the form
<FORM method="get post">	Instructs the browser how to interact with the form URL
<FORM accept="media type">	Defines which MIME types are supported by the server processing the form
<FORM accept-charset="text">	Defines which character sets are supported by the server processing the form
<FORM enctype="media type">	Defines the format of the submitted data
<OPTION>	Defines each menu item
<SELECT name="NAME">...</SELECT>	Generates a pull-down menu
<INPUT type="checkbox">	Generates a check box
<INPUT type="hidden">	Conceals a field from view
<INPUT type="image">	Generates an image that acts like a Submit button
<INPUT type="password">	Generates a one-line password box
<INPUT type="radio">	Generates a radio button
<INPUT type="text">	Generates a one-line text box
<INPUT type="submit">	Generates a Submit button (send form)
<INPUT type="reset">	Generates a Reset button (clear form)